



PCNC 440

Key Dimensions/Weight	
Table Size:	18" x 6.3"
Travel:	10" x 6.25" x 10" (X x Y x Z)
Typical System Weight:	450 lbs.
Recommended Footprint:	42" x 36" (W x D)

Power	
Power Requirements:	115VAC single phase. 15 A breaker recommended.

Frame	
Frame and Table:	Cast iron frame and table, with hand-scraped hydrodynamic ways and tapered adjustment gibs.
Way Surfaces:	Low friction PTFE-filled, Acetyl bonded sliding surface. Similar to Rulon® and Turcite®.



POWERED BY
PathPilot®

- OPTIONS**
- x Deluxe Cabinet Stand
 - x Flood Coolant
 - x 4th Axis **COMING SOON!**
 - x Power Drawbar
 - x Automatic Tool Changer **COMING SOON!**

Motion	
Max Feed Rate:	135 IPM (X,Y), 110 IPM (Z)
Axis Drivers:	High-Performance Bipolar Stepper Motors with Leadshine® Microstepping Drivers
Ballscrews:	Rolled C7 Ball Screw with anti-backlash double ball nut

Spindle	
Spindle Taper:	R8
Spindle Power:	3/4 HP Brushless DC Motor
Spindle Speed:	300 to 10,000 RPM

WWW.TORMACH.COM/440